



# Heading to our 20s

## Some reflections from the BOUSSOLE project

David Antoine  
Vincenzo Vellucci

BOUSSOLE is supported by:





# Let's start with a celebration

On 6<sup>th</sup> September 2018,  
BOUSSOLE buoys had been at sea and had been collecting  
data for an uninterrupted 15 years sequence

Totals, at the end of 2017:

- 5114 days total since 1<sup>st</sup> January 2004
- 4870 days with a buoy at sea (95%)
- 4206 days with data acquisition (86%)

This goes with:


- ~64 days at sea for buoy deployments/recoveries
- ~135 days of on-demand, short maintenance operations







the **200<sup>th</sup>** monthly cruise to the BOUSSOLE site was carried out on 18<sup>th</sup>-19<sup>th</sup> September 2018




**Which means ~440 days at sea**






# Why all this?

## Calibration matters; most recent SVC results



MERIS 4<sup>th</sup> reprocessing




OLCI, preliminary SVC gains




# Why all this?

## Science matters; recent examples



Kheireddine M, Antoine D (2014) Diel variability of the beam attenuation and backscattering coefficients in the north-western Mediterranean Sea (BOUSSOLE site). *Journal of Geophysical Research*, 119, 5465-5482



Barnes M, Antoine D (2014) Proxies of community production derived from the diel variability of particulate attenuation and backscattering coefficients in the northwest Mediterranean Sea. *Limnology and Oceanography*, 59(6), 2133-2149.



# How did we get there?

- 1998 First thoughts about developing an optics mooring
- 1999 Buoy conception & design (->engineering pool tests), in search of funding supports  
1<sup>st</sup> grant from CNES (TOSCA)  
Development essentially made from remainder money from past ESA contracts
- 2000 Construction buoy “v0”, qualification deployment, still in search for funding
- 2001 Start of monthly cruises (July 2001). Hiring first technical staff.  
June 2001: signature of the UPMC/NASA LOA  
First specific ESA funding for BOUSSOLE
- 2002 1<sup>st</sup> deployment of the instrumented buoy → failed (total loss, construction defect)  
Reimbursement by our insurance: continuation of the project  
Complementary engineering studies (IFREMER/MARINTEK) → buoy version 2  
ENVISAT / MERIS launch
- 2003 Construction of the new buoy  
Operational deployment: September 2003
- 2003-.. Operational period (2 sister buoys & instrumentations; rotations every 6 months)  
Progressive development of scientific exploitation of the data
- 2006 Unsuccessful request to being “labelled” as a “SO” at INSU
- 2009 Long-term commitment from CNES (2019 at least) in the frame of Sentinel-3
- 2011 Start of the “BIOCAREX” project funded by ANR (2011-2014)
- 2016 S3A launch
- 2018 S3B launch

....

# Who did this?

<b>David ANTOINE</b>	<b>Chief Scientist</b>
<b>Staff members (100% working for BOUSSOLE)</b>	<b>Project responsibilities</b>
<a href="#">Vincenzo VELLUCCI</a>	Responsible for buoy maintenance and data processing (October 2007 - ongoing)
<a href="#">Melek GOLBOL</a>	Responsible for monthly cruises (March 2013 - ongoing)
<b>Staff members (shared with other activities of our laboratory)</b>	<b>Project responsibilities</b>
<a href="#">Edouard LEYMARIE</a>	Radiance camera development
<a href="#">Joséphine RAS</a>	HPLC and absorption measurements
Céline DIMIER	HPLC and absorption measurements
Edoardo SOTO GARCIA	Maintenance / deployment of the CTD
Vincent TAILLANDIER	Maintenance of the CTD / CDT data processing
<a href="#">Emilie DIAMOND</a>	Responsible for DYFAMED monthly cruises
<a href="#">David LUQUET</a>	Management of diving operations on site
Didier ROBIN	Management of diving operations on site
Guillaume DE LIEGE	Management of diving operations on site, servicing
<b>Past staff members</b>	<b>Project responsibilities</b>
<a href="#">Bernard GENTILI</a>	Data processing codes
Francis LOUIS	Servicing, electronics, design
Grigor BOLENSKY	Maintenance / deployment of the CTD/IOP package
Mustapha OUHSSAIN	HPLC and absorption measurements
Dominique TAILLIEZ	CTD + IOPs, all monthly cruises
Catherine BROWN	Web site design and data base development
Guislain BECU	Responsible for monthly cruises, data processing (2004-2007)
Alec SCOTT	Responsible for monthly cruises, data processing (2003-2004)





# BOUSSOLE: fact sheet

- 18+ years of existence
- 15+ years of operational data production (95% success rate for data acquisition in the 4 years before 2018)
- Currently one of the 2 sites used for vicarious calibration of satellite ocean colour, along with MOBY
- A unique radiometry + optics + BGC data set
- A model for how science & operational objectives come together for mutual benefits
- Permanent effort towards increased data quality (calibration, characterization, QA/QC in general etc...)
- A small, yet highly efficient, technical staff team
- A number of scientific users (publications)
- In good standing to continue for the coming decade







# Progressive improvement in radiometric data quality

- Essentially rely on manufacturer calibration (Satlantic)
- SQM-II: we tried and abandoned
- Immersion coefficients: did some experiments
- Inter-comparison of sensors
- Extrapolation of underwater  $L_u/E_u$  measurements
- Identification and quantification of uncertainty sources
- Better bio-fouling mitigation
- Progressive move from multi- (7  $\lambda$ 's) to hyper-spectral
- Many incremental improvements in data processing (shading, tilt effects, changes of instruments depth, long-term corrections for instrument drifts or biofouling, short-term events identification..)
- Future improvements: cosine response correction, BRDF correction for tilt effects.





# Correcting $E_s$ for tilt



## COSINE CORRECTION OF SURFACE IRRADIANCE

- > First the direct fraction of  $E_s$  is estimated following *Gregg & Carder, 1990*
  - $\overline{E_s(t, \lambda)}' = \overline{E_s(t, \lambda)}' \cdot f_{dir} + \overline{E_s(t, \lambda)}' \cdot (1 - f_{dir})$
- > The correction is then applied to the direct fraction of  $E_s$ 
  - $E_s(t, \lambda) = \overline{E_s(t, \lambda)}' \cdot f_{dir} \cdot f_{tilt} + \overline{E_s(t, \lambda)}' \cdot (1 - f_{dir})$
  - Where  $f_{tilt} = \frac{\cos(\alpha')}{\cos(\alpha)}$









# Shading corrections

## BUOY STRUCTURE SHADING AND INSTRUMENT SELF-SHADING

- > Backward 3D *Montecarlo* simulation (*SimulO*) replaces the *Gordon & Ding (1992)* correction scheme
- > Simulation for each underwater instrument
  - Chl = 0.1, 0.5, 1.0, 5.0  $\mu\text{g l}^{-1}$
  - Azimuth angle from  $0^\circ$  to  $360^\circ$ , with  $5^\circ$  step
  - Zenith angle from  $0^\circ$  to  $90^\circ$ , with  $5^\circ$  step
  - 7 wavelengths (412, 443, 490, 510, 555, 670 nm)
- > A correction factor from LUTs is applied
  - $\overline{L_u(z_4, t, \lambda)} = \overline{L_u(z_4, t, \lambda)'} \cdot f_{s4}$
  - $\overline{L_u(z_9, t, \lambda)} = \overline{L_u(z_9, t, \lambda)'} \cdot f_{s9}$




\_BoueFullLu4m\_443\_0.1 N= 6.0e+09



Shade color bar  
0.2 0.4 0.6 0.8 1 1.2 Azimuth



Shade Average 30–60 deg





# Defining/quantifying uncertainties

## The measurement equation



$$R_{rs} = \frac{\overline{L_{u4}} f_{cal} f_{s4} \exp \left[ z_4 \left( \frac{-\ln(\overline{L_{u9}} f_{cal} f_{s9} / \overline{L_{u4}} f_{cal} f_{s4})}{z_9 - z_4} \right) \right] f_H f_{\rho n}}{\overline{E_s} f_{cal} f_{cos} f_{tilt} f_{dir} + (1 - f_{dir}) \overline{E_s} f_{cal}}$$





# Preliminary error budget

$u$ in % $\lambda$ in nm	$E_s$	$L_{u4}$	$L_W$	$R_{rs}$	$u_{abs}(R_{rs})$
412	2.1	2.6	3.1	3.7	0.000215
443	2.0	2.6	3.1	3.7	0.000225
490	2.0	2.6	3.0	3.7	0.000175
510	2.0	2.6	3.0	3.7	0.000155
560	2.0	2.6	3.1	3.7	0.0000725
665	2.1	3.9	5.9	6.3	0.00000410
681	2.1	4.0	5.9	6.3	0.00000195



# Do we need an “error budget”?

What matters are the uncertainties

How we combine them into a “budget” might actually be confusing, and might be hardly comparable among different systems

What matters for SVC is the number of match-ups with the lowest uncertainty

What matters for validation is the N° of match-up with (maybe) a lightly higher threshold

What matters for science are data with uncertainties below that of the signals to study

The goal: each measurement comes with an uncertainty. Then, it is up to the users to set the uncertainty threshold above which data are rejected.



# Where do we set the bar?

Full characterization and calibration of radiometers is a time consuming and expensive process.

Therefore the question is: can we find the right balance between the effort that we put on calibration/characterisation and the benefit in terms of improved data quality?

Example of the SQM-II: was way too much work for marginal benefit

Corollary: is this where the effort has to be put? Are protocols more important?

And, in the same vein: is a lot of this needed because we do not have the appropriate instruments?



# What about science?

Since inception, BOUSSOLE was conceived as a sustained research activity, rather than as a truly “operational” system.

It has actually become very close to the latter, but still includes a significant research programme

You cannot do otherwise when you operate from a research environment, which in our case is CNRS-INSU-Sorbonne University

It is vital for the motivation of staff

Can provide additional Capex investment





# The challenges we faced in 2018

## Year 2018:

Month	Days with data																															
Jan	<a href="#">1</a>	<a href="#">2</a>	<a href="#">3</a>	<a href="#">4</a>	<a href="#">5</a>	<a href="#">6</a>	<a href="#">7</a>	<a href="#">8</a>	<a href="#">9</a>	<a href="#">10</a>	<a href="#">11</a>	<a href="#">12</a>	<a href="#">13</a>	<a href="#">14</a>	<a href="#">15</a>	<a href="#">16</a>	<a href="#">17</a>	<a href="#">18</a>	<a href="#">19</a>	<a href="#">20</a>	<a href="#">21</a>	<a href="#">22</a>	<a href="#">23</a>	<a href="#">24</a>	--	--	--	<a href="#">28</a>	<a href="#">29</a>	<a href="#">30</a>	<a href="#">31</a>	
Feb	<a href="#">1</a>	<a href="#">2</a>	<a href="#">3</a>	<a href="#">4</a>	<a href="#">5</a>	<a href="#">6</a>	<a href="#">7</a>	<a href="#">8</a>	<a href="#">9</a>	<a href="#">10</a>	<a href="#">11</a>	<a href="#">12</a>	<a href="#">13</a>	<a href="#">14</a>	<a href="#">15</a>	<a href="#">16</a>	<a href="#">17</a>	<a href="#">18</a>	--	--	--	--	--	--	--	--	--					
Mar	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Apr	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
May	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Jun	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Jul	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Aug	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Sep	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Oct	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Nov	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Dec	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Unfortunately, in 2018 the buoy has taken a “gap year”.

The DacNET (central data acquisition system) definitely died, and Satlantic/Seabird were in the process of transitioning their activity from Canada to the US. This has generated unusually long delays for the system maintenance, recalibration etc..



# Why did we end up with this situation?

The DacNET (central data acquisition system) was conceived in the late 1990s, and our units built in 2001-2002.

They have proven extremely reliable, but we warned many times about the need to prepare for replacement.

This was not feasible at constant funding, so it was not done.

Lesson: regular capex investment has to be included at regular intervals in the life of such a long-term activity









# Operations will resume soon





# Inter-comparisons, pre-deployment







# Where to now?



# Radiometry for Ocean Colour **SA**tellites **C**alibration & Community Engagement

# ROSACE

---

Laboratoire d'Océanographie de Villefranche,  
Institut de la Mer de Villefranche



---

Hellenic Centre for  
Marine Research

ACRI-ST

UK National  
Physical Laboratory

University of Tartu,  
Tartu Observatory

CIMEL Electronique






# ROSACE overall logic

COPERNICUS OC-SVC infrastructure preliminary design


ROSACE overall architecture

Overall Governance

EUMETSAT



Field data flow (NRT + delayed modes)



**Uncertainty budget (NMI role)**

Uncertainties from optical system characterization and calibration, Combination of uncertainties from all sources into an end-to-end OC-SVC uncertainty budget, SI-traceability. Support to instrument development

Support - Leadership

Interaction with the International science community, 3<sup>rd</sup> party missions, and international bodies (IOCCG and CEOS OCR-VC)





Thanks for your attention